

STANDARD OPTIONS**DESCRIPTION**

Qty Order Code

1	FREIGHT	Equalized Freight Charge
1	COOLSYS	Cooling Capacity - 7.075 gallon cooling system capacity
1	WARRANTY_05	Warranty - Basic Vehicle-24 months unlimited mileage; Engine-36 months unlimited mileage; Engine-60 month Extended Coverage, 250,000 miles (includes injectors, fuel supply pump and turbo); Emission-60 months 100,000 miles; Frame Rails & Cross Members-48 months unlimited mileage; Cab-48 months unlimited mileage; ABS-24-36 months 300,000 miles.
1	HWATCH_05	Hino Watch Roadside Assistance - 3-year unlimited roadside assistance including lockout, *out of fuel/DEF, battery jumpstart, information, and warranty towing (2 year coverage). *Fluids are customer pay responsibility. Tire Service - assist customer in arranging for roadside tire service if requested
1	FUELTKN	Fuel Tank - Aluminum 50 gallon capacity. Clean CA position. (drivers side mounted)
1	GVWR	GVWR - Gross Vehicle Weight Rating - 33,000 lbs.
1	AIRTANK	Air Tank - Two 34 liter tanks (68L total),(15cfm@1250rpm)
1	BRAKES	Brakes - Full air dual circuit "S" cam type, leading and trailing shoes with automatic adjustment and Antilock Brake System (ABS). Front Brakes: 15.0" diameter x 4.0" x 0.73" thickness: Rear Brakes: 16.5" x 7.0" x 0.85".
1	AIRDRYER	Air Dryer - Bendix -AD-IS (Air Dryer Integrated Solution) heated air dryer.
1	FRAME	Frame - Straight C Channel frame, ladder type, powder coated, 34" wide, yield strength 80,000 PSI, resistance bending moment (RBM) 1,280,800 in./lbs. (one side no reinforcement).
1	WHEELS	Wheels - Accuride powder coated 22.5" x 8.25" 10-stud disc.
1	TIRES	Front tires - Bridgestone 11R 22.5 R268 Rib pattern; Rear tires - Bridgestone 11R 22.5 M726EL Lug pattern.
	AXLES	Front Axle - Meritor MFS12, 12,000 lb. capacity, Reverse Elliot "I" beam with oil lubricated hubs. Rear Axle - Meritor MS21-14X, 21,000 lb. capacity, full-floating single reduction hypoid gearing.
	SPRINGS	Front Spring: Tapered leaf springs with shock absorbers, 12,000 lb. rating; Rear Spring: Semi-elliptical main, 21,000 lb. rating.
1	AXLESTD	Rear Axle Ratio - Standard 5.57

PREMIUM/UPGRADE OPTIONS**DESCRIPTION**

1	338-19V	271" WB / 203.6" CA
1	HBGRDS25	Auto - Allison 2500RDS w/Syn Fluids (PTO). w/ FuelSense
1	ALT135A	Alternator - Delco 12 volt 135 amp Brushless Type
1	Z01DIF	Differential Oil - Synthetic Oil for Rear Differential Road Ranger FE 75W-90
1	SEAT2V	Vinyl, w/single man passenger seat - reclining.

**PREMIUM/UPGRADE
OPTIONS**

DESCRIPTION

Qty	Order Code	
1	PWDL	Power Windows & Power Door Locks.
1	XSWTCH	Additional Dash Switch
1	MTL SC	Material Surcharge
1	SAFETY	Fire Extinguisher ABC 2.5MP, Triangle Kit (17 1/4" wide x 16 1/2" high).
1	HOOK2	Bumper Hook - 2 Hooks

**DELIVERY DATE OF TRUCK
TO OWNER**
